


Drip line with flat pressure compensating dripper




Series:

- 2716 - 2720 - 2723 **PC**
- 2816 - 2820 - 2823 **PC AS**
- 2916 - 2920 - 2923 **PC AS ND**

- All the advantages of a round dripline packed inside a compact bobbin
- Made with 100% virgin raw materials
- Suitable for multi-seasonal, sub-irrigation and greenhouse application
- Resistant to UV, acid and common agricultural chemicals
Dripper available in the following styles:
 - **pressure-compensating PC**
It keeps the same flow rate at different pressures in all the dripline emitters. Suitable for projects on slope.
 - **anti-siphon PC AS**
It avoids the suction of debris during the dripline discharge. Suitable for sub-irrigation and soil laying projects. **Requires the installation of a double-acting vent valve on each sector.**
 - **no-drain PC AS ND**
The emitter closes at 0.25 (bar) to avoid water emission at the end of the irrigation cycle and to reduce the dripline filling time to the next irrigation cycle. Suitable for looping irrigation.
 - **self-cleaning**
The anti-deposit silicone membrane and the large maze one guarantee the continuous cleaning of the dripper.


Drip tape specifications

Nominal diameter	Internal diameter	Outside diameter	Wall thickness		Max pressure
	mm	mm	MIL	mm	Bar
16	13.80	15.00	24	0.60	2.50
		15.20	28	0.70	2.80
		15.40	32	0.80	3.00
		15.60	36	0.90	3.50
		15.80	40	1.00	3.50
20	17.60	19.40	36	0.90	3.00
23	20.80	22.60	36	0.90	3.00



Dripper specifications

Dripper flow rate: (l/h ad 1 Bar)	1.0 - 1.6 - 2.4 - 3.8
Standard spacing : (cm)	10 - 15 - 20 - 25 - 30 - 33 - 40 - 50 - 60 and more...
Special spacing :	groups by request




Dripper data






Nominal flow rate		l/h	1,00	1,60	2,40	3,80
Coefficient of variation CV		%	3,60	6,60	3,50	3,50
Costant K		bar	1,00	1,60	2,30	3,60
Exponent		X	0,0	0,0	0,0	0,0
Maximum working pressure		bar	4,0	4,0	4,0	4,0
Minimum working pressure		bar	0,5	0,5	0,5	0,5
Closing pressure*		bar	0,25	0,25	0,25	0,25
Dripper flow path	Depth	mm	0,76	0,85	0,90	0,90
	Width	mm	0,82	1,06	1,19	1,30
	Length	mm	139,0	132,0	89,6	78,7
Filtration area		mm ²	37,37	37,37	37,37	37,37
Filtration degree		mesh	150	120	120	120
		micron	100	130	130	130

*only pc as nd

Flow rate



Packaging and shipping

 bobbin	400 (m) Re. duralex PC 16/36 30cm (purely indicative data)
 Pallet	small 32 bobbins 114x114xh190 cm maxi 40 bobbins 114x114xh252 cm
 truck	22 maxi pallets 880 bobbins
 container	10 small pallets 320 bobbins
 container	20 maxi pallets 800 bobbins

Fittings

PE starter		5563	16
		5565	20
drill hole 8 mm		9653	23
PVC starter with grommet		4782	16
		4887	20
Coupling		5083	16 x 16
		5471	20 x 20
		9867	23

For other fitting see durafitting

The information contained in this catalog is purely indicative. Aster reserves the right to modify it at any time and in no case can it be held responsible for errors in the data contained in this document.

Maximum recommended length on flat terrain (m)

Nominal diameter	Inside diameter (mm)	Flow rate (l/h)	Spacing (cm)													Pressure (bar)
			10	15	20	25	30	33	40	50	60	75	80	90	100	
16	13.80	1.0	67	95	120	144	167	180	208	246	281	332	347	377	406	1.5
			76	108	138	166	191	206	239	283	324	381	399	434	468	2.0
			91	129	164	197	228	246	285	338	386	455	476	518	558	3.0
		1.6	49	69	88	106	122	132	153	181	207	244	255	277	299	1.5
			56	80	101	122	141	151	176	208	238	281	294	319	344	2.0
			67	95	121	145	167	181	210	249	284	335	350	382	411	3.0
		2.4	37	53	67	81	94	101	117	139	158	187	195	212	229	1.5
			43	61	77	93	108	116	135	160	182	215	225	245	264	2.0
			51	72	92	111	128	138	160	190	218	257	269	293	315	3.0
		3.8	28	39	50	60	70	75	87	103	118	139	146	158	171	1.5
			32	45	57	69	80	86	100	119	136	160	167	182	196	2.0
			38	54	68	82	95	103	119	141	162	191	199	217	234	3.0
20	17.60	1.0	97	139	178	214	248	268	313	372	427	504	529	576	621	1.5
			111	159	204	246	295	308	359	427	490	579	607	661	714	2.0
			131	189	242	292	339	366	427	508	584	690	724	788	851	3.0
		1.6	69	99	127	154	179	193	224	267	307	362	380	414	446	1.5
			80	114	146	177	205	221	258	307	353	416	437	476	514	2.0
			94	136	174	210	244	264	307	366	421	497	521	568	613	3.0
		2.4	53	76	97	118	136	148	172	205	235	278	291	317	342	1.5
			61	87	112	135	157	169	198	235	270	320	334	364	394	2.0
			72	104	133	161	187	202	235	280	322	381	399	436	470	3.0
		3.8	39	56	72	87	101	110	128	152	175	206	216	236	255	1.5
			45	65	83	100	116	126	146	175	200	237	249	271	293	2.0
			53	77	98	119	138	149	174	208	239	283	297	323	349	3.0
23	20.80	1.0	121	174	224	271	315	341	398	475	547	648	680	742	801	1.5
			138	200	257	311	362	391	457	546	628	744	781	852	920	2.0
			164	237	305	369	430	465	544	649	748	887	930	1015	1097	3.0
		1.6	88	128	164	199	231	250	292	349	402	476	499	545	589	1.5
			101	146	188	228	265	287	336	401	461	547	574	626	677	2.0
			120	174	223	271	315	341	399	477	550	651	684	746	806	3.0
		2.4	68	98	126	152	177	191	224	268	308	365	383	418	452	1.5
			77	112	144	174	203	220	257	307	353	419	440	481	519	2.0
			92	133	171	207	242	261	306	366	421	500	524	572	619	3.0
		3.8	52	75	97	118	137	148	174	207	239	283	297	324	350	1.5
			59	84	108	132	153	166	194	232	267	317	332	363	392	2.0
			65	93	120	146	170	183	214	257	295	350	367	400	433	3.0